

# Intercomp CS™ 750 Crane Scale



## STANDARD FEATURES

- Digital calibration
- Adjustable, auto shut off
- 1 in LCD digital readout
- Powered by 6 D cell batteries
- Infrared remote control
- Automatic backlight

## SPECIFICATIONS

**Resolution:**

20 bit A/D delivers more than 1 million internal counts

**Controls:**

Zero, On, Off, Backlight

**Display:**

1 in (25 mm) 5-digit LCD

**Indicators:**

lb/kg

**Power:**

(Batteries are not included) six D size disposable alkaline dry cell, 250 hours or rechargeable nickel-cadmium cell, 80 hours

**Dimensions:**

Control box: 8.5 in L x 5 in W x 4.25 in H  
(216 mm L x 127 mm W x 108 mm H)  
Lifting eye to hook: 9.5 in (241 mm)

**Enclosure:**

Weatherproof extruded-aluminum case

**Est. Ship Weight:**

8.5 lb (4 kg)

**Auto Shut-off:**

Low battery, or after twenty minutes without use

**Accuracy:**

±0.1% of reading

**Temperature:**

Operating -4°F to 140°F  
(-20°C to 60°C)

**Nominal Overload:**

200% of capacity

**Maximum Overload:**

500% of capacity

**Warranty:**

One-year limited warranty


**Approvals:**

NTEP CC 97-135, Class III 3000d  
Measurement Canada AM-5228  
CE


## APPROVALS



Measurement  
Canada  
Approved



REAR VIEW



SIDE VIEW

## PART NUMBER/PRICE

PART #	DESCRIPTION	EST. SHIP WEIGHT	PRICE
43643	CS750, 100 lb (50 kg) x 0.05 lb (0.02 kg)	9 lb	Consult
43644*	CS750, 300 lb (150 kg) x 0.1 lb (0.05 kg)	9 lb	Consult
43645*	CS750, 500 lb (250 kg) x 0.2 lb (0.1 kg)	9 lb	Consult
43646*	CS750, 1,000 lb (500 kg) x 0.5 lb (0.2 kg)	9 lb	Consult

Batteries not included

## OPTIONS/ACCESSORIES

PART #	DESCRIPTION	PRICE
43939	RS-232 serial output	Consult
43941	120/220V external charger (batteries not included) for qty 3x3 D-Nicad/NiMH	Consult
97447	Battery pack, qty 2x3 D-size-Nicad	Consult

\*NTEP and Measurement Canada Certified