



Picture is a representation of actual product

SPECIFICATIONS:

Full Scale Output:	3.0 mV/V +/-1%
Bridge Resistance:	350 ohms, nominal
Material/Finish:	Stainless steel
Temperature:	Compensated range 10°F to 120°F/-12°C to 49°C
Safe Overload:	150% Full scale
Rated Excitation:	10V DC (15V maximum)
Linearity:	0.05% Full scale
Repeatability:	0.03% Full scale
Insulation Resistance:	5000 megohms
Seal Type:	Environmentally IP67
Cable Length:	40' polyurethane jacket*
Cable Color Code:	Green + Excitation Black - Excitation White + Signal Red - Signal

Warranty: Two-year limited warranty

Approvals:



DIMENSIONS

Rated Capacity	A	B	C	ØD	E	F	W	H
lb/inches								
5000-10,000	2.00	6.50	1.00	1.05	4.50	2.38	1.37	.075
25,000	2.75	8.00	1.38	1.55	5.25	2.88	2.00	1.00
50,000-75,000	3.25	14.00	2.50	2.31	9.00	5.00	3.00	1.75
100,000-150,000	4.00	16.00	2.88	2.88	10.25	6.25	4.00	2.00
200,000	6.00	18.00	3.25	3.38	11.00	6.50	4.75	2.38
250,000	6.50	20.00	3.75	3.88	12.50	7.50	5.00	2.75
300,000-500,000	7.50	24.00	5.00	4.31	15.00	9.50	5.40	3.00

RL2010 Order Information

Load Rating	Part#	Price
5000 lb (2268.0 kg)	117731	Consult
10,000 lb (4535.9 kg)	117732	Consult
25,000 lb (11,334.8 kg)	117733	Consult
50,000 lb (22,679.6 kg)	117735	Consult
75,000 lb (34,019.4 kg)	117736	Consult
100,000 lb (45,359.4 kg)	117737	Consult
150,000 lb (68,038.9 kg)	117738	Consult
200,000 lb (90,718.5 kg)	117739	Consult
250,000 lb (113,398.0 kg)	117740	Consult
300,000 lb (136,077.7 kg)	117741	Consult
500,000 lb (226,796.2 kg)	117742	Consult

*40' Cable w/connector

