



Industrial Weighing Systems

9 Richmond St. Picton, ON Canada K0K 2T0

Ph: 613-786-0016 Cell: 613-921-0397 Fax: 613-476-5293

E-mail info@iwsystems.ca Website: www.iwsystems.ca

TOTALCOMP TRWS DIGITAL INDICATOR

Features

The TRWS Stainless Steel Waterproof Digital Indicator is compact and easy to setup. Capable of powering up to 4-350 load cells, this simple device can handle a multitude of functions.

Typical Applications:

Check Weighing, Accumulation,
Over/Under and Animal Weighing.



Backlit LCD display with 22mm digits
Stainless IP65 watertight housing
6 mechanical switch keys
Internal resolution: 1/600,000

Full RS-232 port can transmit data on demand or continuously to match the input requirements of a wide variety of peripheral devices including miniprinters, label printers and computers.

Size: 4.63"H x 7.75"W x 3.25"D

Display 6 digit 22mm LCD with backlight	Display Annunciators lb, kg, g, oz, tj, hj, mt, hi, ok, lo, %, Peak, Battery, Hold, Stable, Auto, Animal, Zero, Tare, Net, Gross	Operating Temp 0° C ~ + 40° C
Load Cell Excitation ±5 VDC, 150 ma	Load Cell Current Drives up to four 350 Ω Load Cells	Signal Input Range 0 to 15 mV 0.5 mV/div
ADC Sigma Delta	Conversion Rate Update max 60 times per sec 1, 2, 5, 10, 20, 50 div	ADC Update <1/10 second
Max. Divisions 30,000d	Key Functions Units, Print, G/N, Tare, Zero, On/Off	Accuracy 0.01% full scale
Output RS232	Power AC adapter (9V/800mA) Ni-MH batteries (1.2V/1200mAhx6)	Gross Weight 2 lbs