



## i-7017Z

10 Differential / 20 single ended Input Module



### Analog Input

Input Channels	10 differential or 20 single-ended, software selectable
Input Type	+/-500mV, +/-1V, +/-5V, +/-10V +/-20mA, 0~20mA, 4~20mA (jumper selectable)
Resolution	16-bit (Normal Mode) / 12-bit (Fast Mode)
Sampling Rate	10 samples/ second (Normal Mode) / 60 samples/ second (Fast Mode) total
Accuracy	+/-0.1% (Normal Mode) / +/-0.5% (Fast Mode) or better
Band Width	15.7Hz (Normal Mode) / 78.7Hz (Fast Mode)
Zero Drift	+/-20uV/°C
Span Drift	+/-25ppm/°C
Input Impedance	Voltage: 2M Ohms(Differential), 1M Ohms(Single-ended) /Current: 125 Ohms
Common Mode Rejection	86dB min.
Normal Mode Rejection	100dB
Over Voltage Protection	Differential: 240 Vrms, Single-ended: 150Vrms
ESD Protection	4KV Contact for each terminal, and 8KV Air for random point
EFT Protection	4KV to Power, and 1KV to RS-485
Intra-module Isolation, Field to Logic	3000 VDC
<b>Interface</b>	
Interface	RS-485
Format	N, 8, 1
Baud Rate	1200 ~ 115200bps
<b>LED Display</b>	
1 LED as Power/Communication indicator	
<b>Power</b>	
Input	+10 to +30 VDC
Power Consumption	2.0W
<b>Environment</b>	
Operating temperature	-25 to 75°C
Storage temperature	-40 to 85°C
Humidity	5 to 95%, non-condensing

## Industrial Weighing Systems

9 Richmond St. Picton, ON Canada K0K 2T0

Ph: 613-786-0016 Cell/Local: 613-921-0397 Fax: 613-476-5293

E-mail [info@iwsystems.ca](mailto:info@iwsystems.ca) Website: [www.iwsystems.ca](http://www.iwsystems.ca)