

## Analog Input RTD

Input Channels	3
Input Type	RTD
Wire connection	2/3/4 wire
RTD Type	Pt100, Ni120, Pt1000
Resolution	16-bit
Sampling Rate	15/12.5 samples/sec filter at 60/ 50Hz
Accuracy	+/-0.1%
Band Width	15.7Hz
Zero Drift	+/-0.5uV/°C
Span Drift	+/-25uV/°C
Common Mode Rejection	150dB min
Normal Mode Rejection	100dB min
Open Wire Detection	Yes
Intra-module Isolation, Field to Logic	3000 VDC
<b>Interface</b>	
Interface	RS-485
Format	N, 8, 1
Baud Rate	1200 ~ 115200bps
<b>LED Display</b>	
1 LED as Power/ Communication indicator	
4 1/2 digits (for i-7033D)	
<b>Power</b>	
Input Voltage Range	+10 to +30 VDC
Power Consumption	1.0 W (i-7033) / 1.6W (i-7033D)
<b>Environment</b>	
Operating temperature	-25 to 75°C
Storage temperature	-40 to 85°C
Humidity	5 to 95%, non-condensing



### i-7033D

3-channel RTD Input Module

Type Code	RTD Type	Temperature Range °C
20	Platinum 100, a= 0.00385	-100 ~ 100
21	Platinum 100, a= 0.00385	0 ~ 100
22	Platinum 100, a= 0.00385	0 ~ 200
23	Platinum 100, a= 0.00385	0 ~ 600
24	Platinum 100, a= 0.003916	-100 ~ 100
25	Platinum 100, a= 0.003916	0 ~ 100
26	Platinum 100, a= 0.003916	0 ~ 200
27	Platinum 100, a= 0.003916	0 ~ 600
28	Nickel 120	-80 ~ 100
29	Nickel 120	0 ~ 100
2A	Platinum 1000, a = 0.00385	-200 ~ 600
2E	PT 100, a= 0.00385	-200°C ~ +200°C
2F	PT 100, a= 0.003916	-200°C ~ +200°C
80	PT 100, a= 0.00385	-200°C ~ +600°C
81	PT 100, a= 0.003916	-200°C ~ +600°C

## Industrial Weighing Systems

9 Richmond St. Picton, ON Canada K0K 2T0

Ph: 613-786-0016 Cell/Local: 613-921-0397 Fax: 613-476-5293

E-mail [info@iwsystems.ca](mailto:info@iwsystems.ca) Website: [www.iwsystems.ca](http://www.iwsystems.ca)